

TSUGAMI B0205E-III

Tipo : Torno de cabezal movil cnc

Marca : TSUGAMI

Modelo : B0205E-III

Año : 2015

N° Serie : 21009A

N° Stock : 10486



CARACTERÍSTICAS TÉCNICAS

- Number of axes : 5
- Number of spindles : 2
- MAIN SPINDLE
 - Max. bar diameter : 20 [mm]
 - Max. machining length : 210 [mm]
 - Spindle speeds : 200 - 10000 [rpm]
 - Spindle power : 2.2 / 3.7 [kW]
 - C axis indexing precision : 0.001 [°]
- COUNTER-SPINDLE
 - Max. bar diameter : 20 [mm]
 - Spindle speeds : 200 - 12000 [rpm]
 - Spindle power : 2.2 / 3.7 [kW]
 - C axis indexing precision : 0.001 [°]
- GUIDE BUSH HOLDER 1
 - Number of positions : 5
 - Number of motorized positions : 3
 - Live tools speed : 8000 [rpm]
- GUIDE BUSH HOLDER 2
 - Number of positions : 3
- END ATTACHMENT
 - Number of positions : 8
- SECONDARY OPERATION
 - Number of positions : 4
 - Number of motorized positions : 2

Tipo : Torno de cabezal movil cnc

Marca : TSUGAMI

Modelo : B0205E-III

Año : 2015

N° Serie : 21009A

N° Stock : 10486

- Live tools speed : 8000 [rpm]

POWER SUPPLY

- Total installed power : 11 [kVA]

WEIGHT & DIMENSIONS

- Machine floor space : 1655 x 1125 [mm]

- Machine height : 1700 [mm]

- Machine weight : 2000 [kg]

MACHINE HOURS

- Number of working hours : 13.837 [h]

EQUIPAMIENTO

- CNC : Fanuc Oi-TD

- 3 colors status lamp

- Rotating guide bush

- Parts catcher

- Parts conveying strip

- Ejection of workpiece

- Chips conveyor

- Coolant tank

* with high-pressure pump : 70 [bars]

- Bar loader : IEMCA ELITE 220 E / 32 LL

- Fire extinguisher *

NB : working order not guaranteed. To have it checked by a qualified organization of the buyer.

- Electric transformer