

ESCOMATIC D6R

Tipo : Torno monohusillo
Marca : ESCOMATIC
Modelo : D6R
N° Serie : 2419
N° Stock : 9105



CARACTERÍSTICAS TÉCNICAS

- Revolver tool number	: 4
- Max. spindles drilling, tapping, threading	: 32 [mm]
- Max. spindle counter-collet	: 36 [mm]
- Max. tapping / threading diameter	
steel	: 4 [mm]
brass	: 5 [mm]
- Max. tapping / threading length	: 25 [mm]
- Max. drilling spindles clamping diameter	: 6 [mm]
- Max. counter-collet clamping diameter	: 6.35 [mm]
- Drilling spindle rotation speeds	: 25, 40, 65, 100, and 150 x 100 [Rpm]
- Tapping / threading spindle speeds	: 6, 9, 13, 20 and 30 x 100 [Rpm]
- Changing time revolver head position (1/4 turn)	: 1/4 [sec]
- Levers report	
drilling	: 1/1
counter-collet in revolver head	: 1/1
self tapping screw thread (director thread)	: 1/3
- Main motor	
power	: 2.2 [kW]
normal speed	: 2820 [Rpm]
- Normal motor tapping / threading	
power	: 0.45 [kW]
normal speed	: 1380 [Rpm]
- Floor space	
without brushholder	: 900 x 1800 [mm]

Tipo : Torno monohusillo

Marca : ESCOMATIC

Modelo : D6R

N° Serie : 2419

N° Stock : 9105

with brushholder : 900 x 3400 [mm]

- Weight (without packing) : 1090 [kg]